

SL32

Thermal Label Printer



- Install the driver with one-click without setting
The factory default is 76 × 130 shipping label
- Simplify the structure to avoid wrong operation
- Anti sticking paper function
- The print speed of the new model is increased by 25% one label per second



Simplify the structure to avoid wrong operation



Anti sticking function to increase the print speed



The print speed is increased by 25%, One label per second

The Details Show



Specification

Item	Parameter	
Printing	Printing	Direct thermal
	Resolution	203 DPI (8 dots/mm)
	Printing Speed	4 level, 180mm/s
	Printing Width	80mm
	Printing Length	25mm-300mm
CPU	32-bit RISC CPU	
Memory	RAM	≥2MB
	Flash	≥2MB
Detection	Sensor	Paper Out sensor, gap sensor, head-up sensor, black mark sensor
Media	Types	Fold paper or roll paper, continuous paper, label, black mark paper, die cut paper
	Width	25mm- 80mm
	Thickness	0.003' ' (80μm) - 0.0087' ' (220μm)
	Core Diameter	1' ' (25.4mm), 1.5' ' (38.1mm)
	Roll Paper Diameter	Max. Φ100 mm (O.D.)
Protocols	TSPL	
Software	Label Design Software	Hmark
	Driver	Windows 2000,Win7,8,10
Resident Fonts	Chinese: GBK FontA 12x12dots, FontB 24x24dots English: ASCII 8×16, 12×24dots	
Barcodes	1D	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5 EAN-8,EAN-13,EAN-128, UPC-A, UPC-E
	2D	PDF-417, QR code
Interfaces	USB and Ethernet or USB and Bluetooth	
Control Panel	One feed button with 5 color indicator LEDs	
Power Supply	Adapter	Input: AC 220 V output: DC 24 V / 1.5 A
Environment	Operation	41°F(5°C)-104°F(40°C), 30%-85%, non-condensing
	Storage	-4°F(-20°C)-122°F(70°C), 10%-90%, non-condensing
Physical Characteristic	Dimension	206*155*133.5mm (L*H*W)
	Weight	1.04kg
Reliability	TPH 30 KM	
Options & Accessory	External fold paper holder, external paper roll holder	
Agency Approval	CCC, CE, FCC	



Your Future, Printed

Xiamen Hanin Co.,Ltd.

Address: 1-5F, NO.8,Gaoqi South 12th Road,Xiamen,China

Telephone: +86-(0)592-5885993 (English)

E-mail: overseas@hpert.com

Website: www.hpert.com

Brochure Version:202402



HPRT Official Website